

## SMW LNB DRO



## Low phase noise single band DRO LNB

The extremely low phase noise ensures the lowest possible BER. Comes standard with Low Noise Figure and F-connector output.

All our LNBs are individually hand tuned to get the very best performance available for each unit. Quality and long term reliability is also essential. Therefore are all LNBs tested according to a very extensive test program, which includes heating, cooling, water-proof testing and rigorous electrical testing.

Swedish Microwave (SMW) was founded 1986 and is today a leading manufacturer of professional LNBs (Low Noise Blockdownconverters). The company is located in Motala Sweden, and to date the products are installed in more than 80 countries.

All work is in-house allowing custom-design products, short delivery times, high flexibility, quick service and support.

## Specification SMW LNB DRO

SMW Frequency range

LO frequency Output frequency

LNB DRO 10.75

LNB DRO 9.75

10.7 - 11.8 GHz

950 - 2050 MHz

9.75 GHz

11.7 - 12.75 GHz 10.75 GHz 950 - 2000 MHz

LNB DRO 10.0 10.95 - 12.1 GHz 10.0 GHz

950 - 2100 MHz

LNB DRO 10.6 11.7 - 12.75 GHz 10.6 GHz 1100 - 2150 MHz

SMW

Frequency range LO frequency Output frequency

LNB DRO 11.3 12.25 - 12.75 GHz 11.3 GHz 950 - 1450 MHz

General specification

Gain typical Gain variation

Noise Figure, typical LO stability (over temp.) Age drifting LO Phase noise typical

LO radiation Image rejection 1 dB gain compression point Input

Output Waterproof Output VSWR DC power

Operating temperature Storage temperature Dimensions Weight

Enclosed accessories

SMW LNB DRO 54 dB

±3 dB within band ±0.3 dB within 30 MHz

0.8 dB

±3 MHz (for LO stability see PLL ±250 kHz)


±500 kHz/year -75 dBc @ 1 kHz -85 dBc @ 5 kHz -95 dBc @ 10 kHz -110 dBc @ 100 kHz -120 dBc @ >1 MHz -60 dBm 50 dB min +5 dBm +15 dBm


WR-75 waveguide F-connector 75 ohm


2.0:1 12 - 24 V 145 mA typ -30 to +60°C -40 to +80°C 122 x 56 x 44 mm 220 g (F), 236 g (N)

O-ring

Screw M4 x 8 4 pcs











Fax. +46 141 21 52 24 e-mail: info@smw.se

Website: http://www.smw.se

